
Handle Operation Instructions





Handle Operated Locks

B-TV, G-TS, C-TS, G-TA

Handle Position	Importance
8	When the handle is pushed up, all locking elements (pin, bolts, hooks) are activated.
	In the basic handle position, the door lock can be locked by a double 360° rotation (in the locking direction) or unlocked (against the locking direction). If the cylinder is used for locking, the handle will be blocked.
	To open the door, push the handle downwards.

Cylinder Operated Locks

Z-TS, Z-TF, Z-RS

Handle Position	Importance
2x -	In the basic handle position, the door lock can be locked by a double 360° rotation (in the locking direction) or unlocked (against the locking direction).
	Open either by handle or cylinder.

Misuse ①



The following illustrations show various misuse operations that must be prevented!

Misuse	Importance
(!)	Never close the door with the latch outside! The latch would be thereby damaged, and the door can no longer be closed!
<u>.</u>	Never paint the hardware or components. Paints and varnishes penetrate the moving fitting parts and prevent proper functionality!
(!)	Keys may only be used with the hand. Never use any kind of tools for this! Bent or broken keys mean that doors can no longer be locked or unlocked.
(!)	Never operate the handle and cylinder lock at the same time! Otherwise, the lock mechanics will be damaged, and the door can no longer be locked or unlocked!
(!)	Never use excessive force on the handle! Forces above 15kg on the handle will damage the handle or the lock mechanism!
(!)	As soon as traces of forced use are visible, the lock or the handle must be replaced!